

PRO-1760FIR Infrared, Vandal Resistant Camera



- 1/3" Sony Super HAD CCD
- 3.8mm Lens
- 600 lines of horizontal resolution
- 0.00 Lux with IR
- 12 volt Power Required
- IR distance up to 45'

Specifications

Signal System	NTSC
Scanning System	2:1 Interlace
Scanning Frequency(H)	15.734kHz
Scanning Frequency(V)	59.94Hz
Image Sensor	1/3" SONY Super HAD CCD
Total Pixels Number	811(H) x 508(V) 410K
Effective Pixels Number	768(H) x 494(V) 380K
Horizontal Resolution	600 TV lines
Video Output Level	1.0 Vp-p (75Ω, composite)
S/N Ratio	More than 48dB (AGC off)
Lens	Fixed Lens (f=3.8mm)
Angle of View	66°
Min. Illumination	0.00 Lux (IR LED on)
White Balance	Auto
AGC	On/Off
BLC	On/Off
Flickerless	On/Off
Electronic Shutter Speed	1/60~10,000sec
IR LED & Sensor	850nm (30°) IR LED 12EA, Sensor 1EA
IR LED Lighting Distance	Max. 15m (Indoor, when using EXview HAD CCD)
Input/Output Connector	Power input(red jack), Video output(yellow jack)
Power Voltage	12VDC
Dimensions	62.0(Ø) x 123.0(H) mm
Weight (Net)	Approx. 600g